

HEALTH	2
FLAMMABILITY	3
REACTIVITY	0

Section 1: IDENTIFICATION

Product Name:	
Product Number:	
CAS-No.:	

Recommended Use:

Manufacturer:

Emergency Telephone No.:

Flavorings

0241400 141-78-6

Ethyl Acetate, Natural

Aurochemicals 7 Nicoll Street Washingtonville, NY 10992 – USA 845-496-6065 845-496-6248 Fax

e No.: 1-800-535-5053

(International 1-352-323-3500 collect)

Section 2: HAZARD(s) IDENTIFICATION

Chemical Classification:

GHS Classification

Hazard Statement:

Flammable Liquids (Category 2) Serious Eye damage/irritation (Category 2A) Specific target organ toxicity-single exposure (Category 3) central nervous system

H225 Highly flammable liquid and vapor

H319 Causes serious eye irritation

Pictogram or written description

Signal Word: Precautionary Statement (s) H336 May cause drowsiness or dizziness



- P210 Keep away from heat/sparks/open flames/hot surfaces No smoking
- P233 Keep container tightly closed
- P240 Ground/bond container and receiving equipment
- P241 Use explosion proof electrical/ventilation/lighting equipment
- P242 Use only non-sparking tools
- P243 Take precautionary measures against static discharge
- P261 Avoid breathing mist or vapor
- P264 Wash skin thoroughly after handling

0241400 Ethyl Acetate Nat sds.doc



P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/Eye protection/face protection
P381	Eliminate all ignition sources if safe to do so
P303+P361+P353	IF ON SKIN (or hair) Remove immediately all contaminated clothing. Rinse skin with water/shower
P304+P340+P312	IF INHALED: Remove victim to fresh air and keep at rest in a comfortable position for breathing. Call a POISON CENTER or doctor/physician if you feel unwell
P305+P351+P338	IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing
P337+P313	If eye irritation persists – get medical advice/attention
P370+P378	In case of fire: Use appropriate media for extinction
P403+P233	Store in well ventilated place. Keep container tightly closed
P403+P235	Store in a well ventilated place. Keep cool
P405	Sore locked up
P501	Dispose of contents/container in accordance with local/regional/national/international regulations
Hazards not otherwise classified (HNOC)	Static accumulating flammable liquid

Supplemental information Hazard Statement

Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion

Section 3: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients			
Chemical name	Synonym	CAS-No	Concentration (%)
Ethyl acetate	Acetic acid ethyl ester; Ethyl Ester of Acetic Acid	141-78-6	100

Section 4:	FIRST AID MEASURES		
Inhalation		If breathing is difficult, remove to fresh air and keep at rest in a posi breathing. Call a physician if symptoms develop or persist.	ion comfortable for
Skin Contact	V'V'	Remove contaminated clothing. Wash skin with cool water then wit water for several minutes. Get medical attention if irritation develops	
Eye Contact		Remove contact lenses if present and easy to do. Promptly wash e water, lifting eye lids as you rinse. Get medical attention if irritation of	
Ingestion		Call a physician or poison control center immediately. If swallowed, water, (only if person is conscious). Do not induce vomiting. If vom should be kept low so the stomach vomit does not enter the lungs.	
Symptoms of Ex	posure	Irritation of eyes and mucous membranes. Vapors have a narcotic e headache, fatigue, dizziness and nausea.	ffect and may cause
Clothing:		Remove contaminated clothing and wash before re-use	
0241400 Ethyl	Acetate Nat sds.doc	Printed: August 10, 2022	Page 2 of



General Information	Make sure the attending physician is shown the label of the product as well as the Safety Data Sheet
Section 5: FIREFIGHTING MEASU	JRES
Extinguishing Media	Water spray, fog, Co2, Dry chemical or alcohol resistant foam Do not use a solid water stream as it may scatter and spread the fire
Special Firefighting Procedures:	Do not stay in danger zone without self contained breathing apparatus Prevent fire-fighting water from entering surface or ground water Use water spray to cool unopened containers
Special Risks	Highly flammable. Vapors heavier than air. Vapors may travel considerable distance to source of ignition and flash back. Container explosion may occur under fire conditions. Forms explosive mixtures in air Development of hazardous combustion gases or vapors possible in the event of fire – ethanol, acetic acid
Section 6: ACCIDENTAL RELEAS	E MEASURES
Person-related precautionary measures	Do not inhale vapors, Ensure supply of fresh air in enclosed rooms Wear respirator, safety glasses, and chemical resistant gloves. Do not touch damaged containers or spilled material unless wearing protective equipment
Environmental-protected measures	Do not allow to enter drains, or sewage system, avoid release into the environment
Procedures for cleaning / absorption	With absorbent, sweep up and discard in container, set out for disposal.
Ventilate area	After sweep up, wash area and ventilate area well
Section 7: HANDLING AND STOR	AGE
Handling:	Avoid contact with skin, eyes and clothing. Do not handle or store near open flame, heat or other sources of ignition. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Avoid breathing vapor. Avoid prolonged exposure. Wash hands thoroughly after handling

Storage:

Open slowly in order to control possible pressure release. Store tightly closed, in cool, dry well ventilated place – no smoking. Protect from moisture.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:	xposure Limits:		Contains substances with Occupational Exposure Limits			
Chemical	CAS#	Value	Control Parameters	Basis		
Ethyl Acetate	141-78-6	PEL	1400 mg/m3 400 ppm	US. OHSA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)		
Ethyl Acetate	141-78-6	TWA	400 ppm	US. ACGIH Threshold Limit Values		

0241400 Ethyl Acetate Nat sds.doc



Ethyl Acetate	141-48-6	REL	1400 mg.m3 400 ppm	US. NIOSH Pocket Guide to Chemical Hazards			
Appropriate Engineering Controls Use explosion proof ventilation equipment to stay below exposure limits							
Personal Protective E	Personal Protective Equipment: These recommendations are advisory only and must be evaluated by an industrial hygienis and safety officer familiar with the specific situation of anticipated use by our customers. T should not be construed as offering an approval for any specific use scenario.						
Body Protection:		Protective clothing should be selected specifically for the work place, depending on concentration and quantity of the hazardous substances handled. The resistance of the protective clothing to chemicals should be ascertained with the respective supplier					
Respiratory Protection: Required when vapors / aerosols are generated Full face chemical respirator with organic vapor cartridges							
Eye Protection:	e Protection: Wear eye and face protection – Face Shield – Avoid contact with eyes						
Hand Protection:		Wear chemically resistant gloves					
Industrial Hygiene:		Handle in accordance with good industrial hygiene and safety practice. Wash hands after working with product					

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Color:	Liquid Transparent, colorless to pale yellow
Odor:	Brandy, ethereal, fruity
Boiling Point:	77°C
Flashpoint:	-4°C
Melting Point:	N/A
Ignition temperature	426.67°C
Oxidizing Properties:	Not oxidizing; flammable
Lower Explosion Limit	2.1 vol%
Upper Explosion Limit	11.5 vol %
Vapor Pressure:	97 hPa
Specific Gravity @ 25°C:	0.894-0.898
Solubility	Soluble in water; slightly soluble in ethanol, ether, glycol, fixed and volatile oils

Section 10: STABILITY AND REACTIVITY

Conditions to be avoided Substances to be avoided	Heat, flames and sparks. Extremes of temperature and direct sunlight. Alkali metals, fluorine, hydrides, strong oxidizing agents
Hazardous decomposition products:	Formed under fire conditions – ethanol, acetic acid
Further information	Light sensitive; sensitive to air; unsuitable working materials: various plastics. Explosible with air in a vaporous/gaseous state

Section 11: TOXICOLOGICAL INFORMATION



LD50, Oral Rat	4,934 ml/kg
LC50 Inhalation Rat	1600 ppm (v) /6 h
LD50 Dermal Rabbit	>18000 mg/kg
EYE-HMN	400 ppm
Reproductive Toxicity	No data available
Potential Health Effects (Accute	
Effects)	
Skin corrosion/irritation	No data available
Serious eye damage/eye irritation	Causes serious eye irritation
Respiratory sensitization	No data available
Skin sensitization	No data available
Germ cell mutagenicity	No data available
	Not considered to be carcinogen by IARC, ACGIH, NTP or OSHA
Carcinogenicity Reproductive toxicity	No data available
Specific target organ Toxicity-single exposure (GHS)	May cause irritation to the respiratory system – Narcotic effect
Specific target organ toxicity-	No data available
repeated exposure (GHS) Aspiration hazard	No dete qualible
•	No data available
Prolonged exposure can cause:	Nausea, headache and vomiting, narcotic effect, anemia
Target Organs RTECS#	Liver, Kidney, Central nervous system, Blood AH5425000
information.	s of chemicals substances data is represented here. See actual entry in RTECS for complete
Section 12: ECOLOGICAL I	NFORMATION
Ecotoxic effects	
	Aquatic Fish: LC50 Indian catfish (Heteropneustes fossilis 200.32-225.42 mg/l 96h
Further ecological data	Do not allow to enter water, drain or soil
Section 13: DISPOSAL CON	ISIDERATIONS
Product:	According to local regulations
Packaging:	According to local regulations
Section 14: TRANSPORT II	NFORMATION
DOT	UN1173 / Ethyl Acetate Class 3 Packing Group II
Proper Shipping Name	Ethyl acetate
IMDG-Classification	UN1173 / Ethyl Acetate Class 3 Packing Group II EMS F-E, S-D
IATA-Classification	UN1173 / Ethyl Acetate Class 3 Packing Group II

Section 15: REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know SARA 302 Extremely Hazardous Substances Threshold Planning Quantity This material does not contain any components with a section 302 EHS TPQ.

0241400 Ethyl Acetate Nat sds.doc

ADR-Classification

3 / UN1173 / PGII





SARA 311/312 Hazardous Chemicals : Fire Hazard; Acute Health Hazard

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Section 16: OTHER INFORMATION

Aurochemicals provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose. Aurochemicals makes no representations or warranties, either expressed or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly, Aurochemicals will not be responsible, nor held liable, for damages resulting from use of or reliance upon this information.

Issued by:				Contact Person:
Aurochemicals				Deo N. Persaud
7 Nicoll Street			Revised Date:	8/10/2022
Washingtonville, NY 10992 USA				